

Rustler

SETUP SHEET

Driver: _____
 Date: _____
 Event: _____
 Track / City: _____
 Qual. / Finish: _____

TRACK CONDITIONS
 Surface: Smooth Med. Rough
 Traction: High Med. Low
 Size: Tight Med. Open
 Wet: Yes No

FRONT SUSPENSION

TOE ANGLE
 In Out
 Toe-Out 0° Toe-In
 Front
 Stock: 0°

GAMBER
 Negative 0° Positive
 Stock: -1°

RIDE HEIGHT
Arms:
 Above
 Level
 Below

SWAYBAR Yes No
Size: Small Large
 Soft
 Med
 Firm

REAR SUSPENSION

GAMBER
 Negative 0° Positive
 Stock: -1.5°

ROLL CENTER (INSIDE)
 Upper
 Lower
 Stock: Lower

SWAYBAR Yes No
Size: Small Large
 Soft
 Med
 Firm

RIDE HEIGHT
Drive Shafts:
 Above
 Level
 Below

FRONT SHOCKS

MOUNTING POSITION
 Stock: 1 **1** **2**

PISTONS
 1 Hole 2 Hole 3 Hole
 Stock: 2 Hole

Springs (Color) _____
 Stock: White

Oil _____ wt
 Stock: 30wt

1 2

LIMITERS
 _____ mm
 Stock: None

CAPS
 Plastic
 Aluminum
 Stock: Plastic

REAR SHOCKS

PISTONS
 1 Hole 2 Hole (stock) 3 Hole
 Stock: 2

Springs (Color) _____
 Stock: White

Oil _____ wt
 Stock: 30wt

1 2 3 4 5

LIMITERS
 _____ mm
 Stock: 1.5mm

CAPS
 Plastic
 Aluminum
 Stock: Plastic

DIFFERENTIAL

Oil _____ wt Stock: None

TRANSMISSION

Spur Gear _____ T Stock: 86 Pinion _____ T Stock: 18
 Slipper: Soft Medium Firm
 Stock: Medium

ELECTRONICS

Motor: Stock Other _____
 ESC: Stock Other _____
 Battery: _____
 Battery Position: Front Rear Stock: Rear

TIRES / WHEELS

Front _____ Rear _____
 Type _____
 Insert _____
 Wheel _____

BODY

Stock Other _____

CAR / TRACK COMMENTS
