

Rustler

SETUP SHEET

Driver: _____
 Date: _____
 Event: _____
 Track / City: _____
 Qual. / Finish: _____

TRACK CONDITIONS
 Surface: Smooth Med. Rough
 Traction: High Med. Low
 Size: Tight Med. Open
 Wet: Yes No

FRONT SUSPENSION

TOE ANGLE

In Out

Toe-Out 0° Toe-In

Stock: 0°

CAMBER

Negative 0° Positive

Stock: -1°

RIDE HEIGHT

Arms:

Above
 Level
 Below

SWAYBAR Yes No

Size: Small Large

Soft
 Med
 Firm

REAR SUSPENSION

CAMBER

Negative 0° Positive

Stock: -1.5°

ROLL CENTER (INSIDE)

Upper
 Lower

Stock: Lower

SWAYBAR Yes No

Size: Small Large

Soft
 Med
 Firm

RIDE HEIGHT

Drive Shafts:

Above
 Level
 Below

FRONT SHOCKS

MOUNTING POSITION

Stock: 1 1 2

PISTONS

1 Hole 2 Hole 3 Hole

Stock: 2 Hole

Springs (Color) _____
 Stock: White

Oil _____ wt
 Stock: 30wt

LIMITERS

_____ mm
 Stock: None

_____ mm
 Stock: None

CAPS

Plastic
 Aluminum

Stock: Plastic

REAR SHOCKS

MOUNTING POSITION

Stock: 2 1 2 3 4 5

PISTONS

1 Hole 2 Hole (stock) 3 Hole

Stock: 2 Hole

Springs (Color) _____
 Stock: White

Oil _____ wt
 Stock: 30wt

LIMITERS

_____ mm
 Stock: 1.5mm

_____ mm
 Stock: 5mm

CAPS

Plastic
 Aluminum

Stock: Plastic

DIFFERENTIAL

Oil _____ wt Stock: None

TRANSMISSION

Spur Gear _____ T Stock: 86 Pinion _____ T Stock: 18

Slipper: Soft Medium Firm
 Stock: Medium

TIRES / WHEELS

Front _____ Rear _____

Type _____

Insert _____

Wheel _____

BODY

Stock Other _____

ELECTRONICS

Motor: Stock Other _____

ESC: Stock Other _____

Battery: _____

Battery Position: Front Rear Stock: Rear

CAR / TRACK COMMENTS



1100 Klein Rd, Plano, TX 75074
 1-888-TRAXXAS, www.Traxxas.com